

# Grade 100 Alloy Chain



**Spectrum 10<sup>®</sup>**  
Grade 100  
Alloy Chain

- Alloy Steel.
- Heat Treated.
- 25% stronger than Grade 80 Alloy Chain.
- Permanently embossed with CG (Crosby Group) and 10 (Grade).
- Finish - Black rust preventative coating.
- Proof Tested at 2 times the Working Load Limit with certification
- Standard container - fiber drum

## Grade 100 Alloy Chain Recommended for overhead lifting applications

Chain Size		Gr. 100 Stock No.	Meters Per Drum	Dimensions (mm)	Working Load Limit (t)*	Weight Per Meter (kg)
(in)	(mm)					
9/32 (1/4)	7	1210055	200	7 x 21	2.0	1.05
5/16	8	1210076	200	8 x 24	2.5	1.25
3/8	10	1210097	200	10 x 30	4.0	2.20
1/2	13	1210118	150	13 x 39	6.7	3.80
5/8	16	1210139	100	16 x 48	10.0	5.70
3/4	19	1210160	50	19 x 57	14.0	8.03
7/8	22	273867	50	23 x 69	21.0	10.9
7/8	23	1210202	50	23 x 69	21.0	10.9
1	26	1210232	50	26 x 78	26.5	15.2
1-1/4	32	1210250	20	32 x 96	40.0	23.0

\* Proof tested at 2 times Working Load Limit. Ultimate Load is 4 times the Working Load Limit.